



TIRE COMPATIBILITY CHART FOR EASYDRIFT V1.0 200x600

The sizes without any brands attached are only theoretical and haven't been validated. The specified tires have been tested and approved.

Brand		Type	Dimensions				
			Tire			Theoretical diameter	
			Width	Height	Rim (inch)	mm	inch
15	185 / 60 / 15						
	CONTINENTAL	contipremiumcontact2 88H	185	60	15	603,0	23,74
	GENERAL	Altimax RT	185	60	15		
	KLEBER	Dynaxer HP3 88 H-EL	185	60	15		
	ROOTALA	Radial F108 84H	185	60	15		
	205 / 55 / 15						
			205	55	15	606,5	23,88
225 / 50 / 15							
		225	50	15	606,0	23,86	
16	185 / 55 / 16						
			185	55	16	609,9	24,01
	195 / 50 / 16						
	GOODYEAR	Eagle F1 GSD3 84V	195	50	16	601,4	23,68
	205 / 50 / 16						
	ROAD HUGGER	87H SL BSW	205	50	16	611,4	24,07
	MASTERCRAFT	MC440	205	50	16		
	215 / 45 / 16						
			215	45	16	599,9	23,62
225 / 45 / 16							
		225	45	16	608,9	23,97	
17	215 / 40 / 17						
	DUNLOP	SP Sport Maxx 87V	215	40	17	603,8	23,77
	KUMHO	ECSTA SPT ZR17 XL 87W Extra Load	215	40	17		
	KUMHO	ECSTA LE Sport	215	40	17		
	MATADOR	Vectora ZR 83 Y MP 45	215	40	17		
	MICHELIN	Pilot Exalto 87 W Extra Load	215	40	17		
	NANKANG	NS2 87 V	215	40	17		
	PRIMEWELL	PZ-900 87 W	215	40	17		
	ROADSTONE	N3000 87 W	215	40	17		
	SAILUN	Zsr XL	215	40	17		
ZENNA	ARGUS UHP	215	40	17			
18	215 / 35 / 18						
	IMPERIAL	ECOSPORT 84 W	215	35	18	607,7	23,93
	KUMHO	ECSTA PA31 XL 84W	215	35	18		
	NANKANG	NS2 84 W	215	35	18		
	NANKANG	NS20 84 Y	215	35	18		
	ZENNA	ARGUS UHP ZR18XL	215	35	18		

Perimeter= 2Rπ = diameter x π

Diameter= 2R = Perimeter/π

π= 3,14159265359

1 inch = 25,4 mm



Minimum diameter deflated in mm = 598
Maximum diameter deflated in mm = 610
Minimum perimeter deflated in mm = 1878,7
Maximum perimeter deflated in mm = 1916,4

EASYDRIFT V1.0 - Design 2014

WEIGHT [kg]: 7.55

